



Model : **ON-AT5030A** X-Ray Baggage Scanner

Product highlights

- * Linux operation system
- * ARM CPU
- * Digital signal and processor
- * Continuous hard work for 10000 hours
- * Energy saving design
- * High penetration
- * Good quality images



Physical Specifications	
Unit weight (kgs)	250
Unit size (mm)	1660(L)*746(W)*1165(H)
Gross weight (kgs)	320
Packing size	180*88*138cm

General Specifications	
Tunnel size(mm)	503(L)*301(W)
Conveyor Speed(m/s)	0.22
Conveyor height(mm)	668.5
Conveyor Max Load(kgs)	150
X ray dose per each inspection	Typical 3.0 μ Gy, guarantee 3.5 μ Gy
X ray leakage	Typical 2.0 μ Gy/h, guarantee 2.5 μ Gy/h
Penetration	Typical 16mm, guarantee 11mm
Wire Resolution	Typical AWG38, guarantee AWG36
Penetration Resolution	Typical AWG34, guarantee AWG32
Spatial resolution:	Typical dia1.3mm, Vertical: dia1.3mm; Guarantee dia1.6mm, Vertical: dia1.6mm;
Power Consumption	0.5KVA
Noise	< 60 dB
Film Safety	Guarantee ASA/ISO1600 Film

X-ray Generator (single)	
Anode Voltage	80 KV
Anode power	0.3mA
Generate angle	80 degree upward
Generate direct	from bottom to top
Cooling / Duty Cycle	Oil Cooling /100%

Brand	made by ourself
-------	-----------------

Software System	
Self-test after power on	Self test after power-on, and show the problem (1. emergency stop, 2. housing panel is open 3. calibration fail 4. detection system error 5. hard drive is missing)
Image Display	High resolution of 1024 * 1280 pixel;
Image Enhancement	Color/BW, negative, high/low penetration, organic /inorganic Stripping, general enhancement, and pseudo color, etc
Image Recall	30 images recallable, retrieval
Image Archive	Up to 500,000 images stored automatically, enable transferring to USB disk, and converting to JPG, BMP and other general formats
Real-time Curve	Real-time curve to see if the detection system and other components work well
Others	Fault diagnosis, system time setting, detection blind dots delete, x-ray source setting(analogue or digital), alarm setting, images setting, software register, user management, TIP report, data setting(machine working time, x-ray source working time, baggage counter, etc.)

Operating Environment	
Operation temperature/Humidity	5°C-40°C / 0%-90%(non-condensing)
Storage Temperature/Humidity	-40°Cto 70°C / 5%-95%(non-condensing)
Operation Power	220VAC(±10%) 50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)

Computer and other	
Monitor	High Resolution Color, LCD Accord, 17inch
Hard Disk	SEAGATE 500G 3.5"
CPU	Cortex A9
Storage	1GB
Main board	IMX6_mainboard-V030

Compliance	
International	* ISO19001 ; ISO14001 ; OHSMS18001 ; * CE * USA FDA
National	* Health Inspection Report * Computer Software Copyright Registration Certificate * Software Product Registration Certificate * Radiation Safety Certificate from Ministry of Public Security * Quality Certification from Safety and Police Electronic Products Quality Inspection Center

Outlook Size

