

# World Smallest UPS!

## Compact, But POWERFUL!



**A** Omni Supply Series - 10W  
8.5x5.7x4.2 cm

**B** Omni Supply Series - 30W  
10.5x8.0x4.3 cm

**C** Tank Combo Series  
15.3x7.0x3.3 cm

## DC on-line UPS for

IP CAMERA / ROUTER / CCTV  
ACCESS CONTROL SYSTEM /  
OPTICAL FIBER ROUTER / VOIP PHONE



# Internal Lithium-Polymer Battery for long backup time




ON-B2200 / ON-B4400




ON-B5200



ON-B4000 / ON-B6000

MODEL		ON-B4000 / 6000
INPUT	Voltage	AC 85~265 VAC
	Frequency	50 / 60Hz
OUTPUT	Voltage	5 / 7.5 / 9 / 12 Vdc ± 5% selected by Switch
	Power rating	10W
	Ripple	150mV
BATTERY	Type	Lithium-Polymer Battery 4000 mAh & 6000 mAh
PROTECTION	Input	Fuse for Overload & Short Circuit Protection
	Output	MCU for Over Discharge, Overload, Short Circuit Protection
	Battery	Battery Protection IC for Over Charge, Over Discharge, Overload, Short Circuit Protection
INDICATORS	LED	Battery Level x 3, Battery Life x 1
CORD	Input Cord	AC Power Cable (Lenght:1.5m)
	Output Cord	DC Power cord : Jack 5.5mm x 2.1mm 20Awg (Length: 300mm)
ACCESSORY	Connector	F5.5x2.1mm/M5.5x2.5mm ; F5.5x2.1mm/M4.8x1.7mm ; F5.5x2.1mm/M3.5x1.35mm  (Total: 3pcs)
DIMENSION	L x W x H(mm)	153mm x 70mm x 33mm

MODEL		ON-B2200	ON-B4400	ON-B5200
INPUT	Voltage	5V ~12VDC		12V ~24VDC
OUTPUT	Voltage	5V / 7.5V / 9V / 12V Auto-Selection or 12V Single Voltage		12V / 15V / 19V / 24V Auto-Selection or 12V / 15V / 19V / 24V Single Voltage (DC Start)
	Current	10W		30W
BATTERY	Type	Lithium-Polymer Battery		Lithium-Ion 18650 type Battery
	Voltage	3.7V		7.4V
PROTECTION	Capacity	2000mAh	4000mAh	5200mAh
	Output	MCU for Over Discharge, Overload, Short Circuit Protection		
	Battery	Battery Protection IC for Over Charge, Over Discharge, Overload, Short Circuit Protection		
INDICATORS	LED	Power On x 1, Function Alarm x 1, Battery Mode x1 & Auto Detecting I/P Voltage : 5V、7.5V、9V、12VDC		Power On x 1, Function Alarm x 1, Battery Mode x 1
CORD	Output Cord	DC Power cord : Jack 5.5mm x 2.1mm 20Awg 		
ACCESSORY	Connector	F5.5mm x 2.5mm / M5.5mm x 2.1mm & F5.5mm x 2.1mm / M5.5mm x 2.5mm		
		F4.8mm x 1.7mm / M5.5mm x 2.1mm & F5.5mm x 2.1mm / M4.8mm x 1.7mm		
		F3.5mm x 1.35mm / M5.5mm x 2.1mm & F5.5mm x 2.1mm / M3.5mm x 1.35mm		
		(Total: 6pcs)		
DIMENSION	L x W x H(mm)	85mm x 57mm x 42mm		105mm x 80mm x 43mm