

Multi-functions CCTV tester

Model : ON-TM4300S (no SDI)

- ◆ 4.3 inch IPS touch screen, 960*540 resolution
- ◆ H.265/H.264, 4K video display via mainstream
- ◆ Built in WIFI, create WIFI hotspot
- ◆ IP discovery , shortcut button, drop-down menu
- ◆ Rapid ONVIF, auto view video and create testing report
- ◆ RJ45 cable TDR test, cable quality test
- ◆ TesterPlay: Tester, android version mobile phone, PC display at the same time
- ◆ 5MP TVI, 4MP CVI, 5MP AHD test
- ◆ Dual window test, IP & Analog camera test
- ◆ HDMI input, support 1080p*
- ◆ DC12V 2A, DC48V PoE power output
- ◆ Quick office (excel, word, PPT format) doc.
- ◆ UTP cable tester

The 4.3 inch IPS touch screen IP camera tester is designed for maintenance and installation of IP analog, HD coaxial cameras as well as other security equipment. The 960*540 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. Additionally, it has other functions such as RJ45 cable TDR test, POE power & voltage test and UTP cable test etc. CCTV installers often need to carry a variety of testing tools to complete their work. If take the all in one camera tester, making working conditions safer and increasing productivity.

Application

- CCTV system installation and maintenance
- Network cabling project installation and maintenance
- Dome camera, IP TVI CVI AHD SDI 4K H.265 camera testing
- Video transmission channel testing
- PTZ controller

Features

1. New - 4.3 inch IPS touch screen, 960*540 resolution
2. New - H.264 and H.265, 4K video display via mainstream
3. New - 5MP TVI test, 2560x1944P 12.5FPS, 4xzoom, video record and playback, coaxial PTZ control and call camera OSD menu
4. 5MP AHD test, 2560x1944P 12.5FPS, 4xzoom, video record and playback, coaxial PTZ control and call camera OSD menu
5. 4MP CVI test, 2560x1440P 25F/30F, 4xzoom, video record and playback, coaxial PTZ control and call camera OSD menu
6. IP & CVBS camera test, PTZ controller
7. New - Rapid video, just by one key to detect all network cameras and auto display
8. Rapid ONVIF, auto log in and display image from the camera, activate Hikvision camera, and also can create testing report
9. New - IP and analog testing at the same time, converter test from analog to digital with dual test window IP & CVBS
10. New - Screen management, change function's icons order, create new directory
11. New - Shortcut button, drop-down menu, can select PoE power, IP setting, WLAN switch, HDMI IN functions etc in any interface
12. Improvement cable tester, UTP cable, telephone cable etc order and connectivity test, can save testing report, if special number, need customized
13. New - RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc



14. **TesterPlay (screen projection) : tester, android version mobile phone and PC display at the same time**
15. **New- Screen lock**, password lock and pattern lock are optional
16. **New- HDMI signal input**,720×480p /720×576p /1280×720p /1920×1080p /1024×768p/1280×1024p /1280×900p /1440×900p display image ,record and snapshot
17. HDMI output ,support 1080P
18. **New- CVBS loop test** , the tester send and receive color bar generator signal ,to check BNC cable
19. **New- Traffic monitoring** of the tester "LAN port", display network port or WIFI connection real-time upload and download speeds and other network parameters
20. **New- Customers self update software ,you can install apps with android version ,such as Skype, wechat etc**
21. ONVIF camera test, support 4K/h.265/h.264, Network PTZ controller (ONVIF)
22. Built in Wi-Fi ,display image from the wireless camera , **create WIFI hotspot**
23. **New- 4K video files and MKV/MP4 media files play**
24. PoE DC48V power output, Max power 24W,12V /2A power output/5V 2A power output, as a power bank
25. **New- Quick office**, quick office app (support excel ,word ,ppt format) doc. editable
26. 8GB SD card including
27. IP discovery, it can auto-scan the whole network segment IP, and auto-modify tester's IP address
28. Display its genuine resolution of the IP camera images
29. PTZ control supports more than 30 protocols such as PELCO-P, PELCO-D, and SAMSUNG
30. Enhanced Color bar generator, PAL/NTSC multi-system color bar video generator
31. POE voltage measurement, PING test ,IP address scan, port flashing etc
32. Audio in /out , support record and save the audio/LED lamp, calculators, music players and other application tools
33. 7.4 V /5000mAh Lithium Ion Polymer Battery, after 5-6 hours charging , working time lasts 10 hours

Specifications

LCD	Item series	ON-TM4300S	
	Display	New 4.3 inch IPS touch screen ,960*540 resolution	
Video Mode	CVBS	1 channel BNC input & 1 channel BNC looped output, NTSC/PAL (Auto adapt)	
		PTZ control,RS485 control, Baud 600-115200bps,compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc	
		CVBS loop test	the tester send and receive color bar generator signal , check BNC cable
	IP camera test 4k/H.265/H.264	IP Discovery/Quick ONVIF/IPC test /RTSP play /Client APK	
		Rapid Video	Auto view the video, create testing report
		Hik test tool	pressing just one key to activate hikvision camera , Image test, can modify the user name, password and IP parameters
		Dahua test tool	Dahua camera test, modify the user name, password and IP parameters
	IP& CVBS test	IP& CVBS test at the same time ,converter test from analog to digital with dual test window	
	Coaxial HD test	5MP TVI camera test,2560x1944P 12.5FPS, UTC control/ call OSD menu	
		4MP CVI camera test,2560x1440P 25F/30F,UTC control d call OSD menu	
5MP AHD test, 2560x1944P 12.5FPS, UTC control d call OSD menu			
HDMI input	1 channel HDMI input, support 1080P		
Zoom Image	4x zoom, to enlarge image, Screen snapshot, record ,save ,view and record and play back		

Analog Video out	color bar generator	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable
HDMI output	1 channel HDMI output, support 1920*1080P	
	12V/2A power	Output DC12V/2A power out ,supply temporarily power for the camera
Power output	PoE power output	48V PoE power output, max power 24W
	5V/2A power output	USB 5V 2A power output, as a power bank
Cable test	UTP cable test	Test UTP cable connection status and display on the screen. Read the number on the screen
	RJ45 cable TDR test	test cable pair status, length, attenuation, reflectivity, impedance, skew etc. measurement range 180M.
TesterPlay	screen projection: tester, mobile phone and PC display at the same time (For android version mobile phone)	
Network test	Trace route, Link monitor , DHCP server, port flashing , Ping test	
Wi-Fi	Built in WIFI,speeds150M,display wireless camera image	
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone	
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal	
PoE test	Measurement POE switch or PSE power supply voltage and cable connection status	
Drop-down menu	You can select PoE power switch ,IP setting, WLAN switch , HDMI IN functions etc in any interface	
External power supply	DC 12V 2A	
Battery	Built-in 7.4V Lithium polymer battery ,5000mAh	
Rechargeable	After charging 5-6 hours, normal working time 10 hours	
Operation setting	OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc	
Auto off	1-30 (mins)	
Working Temperature	-10℃---+50℃	
Working Humidity	30%-90%	
Dimension/Weight	215mm x 127mm x 53mm / 0.82kg	

Note: The above data is for reference only, subject to change without prior notice.