

Multi-functions CCTV tester New

Model: ON-TMX4 (no SDI)

- ◆ 4 inch IPS touch screen, 800*480 resolution
- ♦ H.265/H.264, 4K video display via mainstream
- Built in WIFI, create WIFI hotspot
- RJ45 cable TDR test, cable quality test
- ◆ Rapid ONVIF, auto view video and create testing report
- Backlight key design, convenient for operate in the dark.
- ◆ Tester Play: Tester, android version mobile phone, PC display at the same time
- ◆ 8MP TVI, 8MP CVI, 5MP AHD test
- ◆ Dual window test, IP &Analog camera test
- ♦ HDMI input, support1080p
- UTP cable tester
- DC12V 2A, DC48V PoE power output
- ♦ HD coaxial video signal quality and level meter test

The 4 inch IPS touch screen IP camera tester is designed for maintenance and installation of IP analog, HD coaxial cameras as well as other security equipment. The 800^*480 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. Additional, it with other functions TDR cable test, Digital multi-meter, UTP cable test and cable scan etc. CCTV installers often need to carry a variety of testing tools to complete their work. If take the all in one camera tester, making working conditions safer and increasing productivity.

Application

- CCTV system installation and maintenance
- Network cabling project installation and maintenance
- Dome camera, IP TVI CVI AHD SDI 4K H.265 camera testing
- Video transmission channel testing
- PTZ controller

Features

- 1. 4 inch IPS touch screen,800*480 resolution
- 2. New- H.264 and H .265 ,4K video display via mainstream
- 3. New- 8MP TVI test,3840 x 2160P 15 FPS,4xzoom ,video record and playback ,coaxial PTZ control and call camera OSD menu *
- 4. 5MP AHD test, 2560x1944P 12.5F/ 20F,4xzoom ,video record and playback ,coaxial PTZ control and call camera OSD menu*
- 5. 8MP CVI test,3840 x 2160P 12.5/15 FPS, 4xzoom ,video record and playback ,coaxial PTZ control and call camera OSD menu*
- 6. IP & CVBS camera test, PTZ controller
- 7. New- Rapid video, just by one key to detect all network cameras and auto display
- 8. Rapid ONVIF, auto log in and display image from the camera, activate Hikvision camera, and also can create testing report
- 9. New- IP and analog testing at the same time, converter test from analog to digital with dual test window IP & CVBS
- 10. New- Screen management, change function's icons order, create new directory
- 11. New- Shortcut button, drop-down menu, can select PoE power, IP setting, CVBS, LAN info, HDMI IN functions etc in any interface
- 12. Improvement cable tester, UTP cable, telephone cable etc order and connectivity test, can save testing report, if special number, need customized
- 13. New- RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc
- 14. TesterPlay (screen projection): tester, android version mobile phone and PC display at the same time
- 15. New- Screen lock, password lock and pattern lock are optional



- 16. New- HDMI signal input,720×480p /720×576p /1280×720p /1920×1080p /1024×768p/1280×1024p /1280×900p /1440×900p display image ,record and snapshot *
- 17. New- CVBS loop test, the tester send and receive color bar generator signal, to check BNC cable
- 18. New- Traffic monitoring of the tester "LAN port", display network port or WIFI connection real-time upload and download speeds and other network parameters
- 19. New- Customers self update software ,you can install apps with android version ,such as Skype, wechat etc
- 20. ONVIF camera test, support 4K/h.265/h.264, Network PTZ controller (ONVIF)
- 21. Built in Wi-Fi ,display image from the wireless camera , create WIFI hotspot
- 22. New- 4K video files and MKV/MP4 media files play
- 23. PoE DC48V power output, Max power 24W,12V /2A power output, as a power bank
- 24. New- Quick office, quick office app (support excel ,word ,ppt format) doc. editable
- 25. 8GB SD card including
- 26. IP discovery, it can auto-scan the whole network segment IP, and auto-modify tester's IP address
- 27. Display its genuine resolution of the IP camera images
- 28. PTZ control supports more than 30 protocols such as PELCO-P, PELCO-D, and SAMSUNG
- 29. Enhanced Color bar generator, PAL/NTSC multi-system color bar video generator
- 30. POE voltage measurement, PING test ,IP address scan, port flashing etc
- 31. Audio in , support record and save the audio/LED lamp, calculators, music players and other application tools
- 32. 7.4 V /4000mAh Lithium Ion Polymer Battery, after 3~4 hours charging , working time lasts 9 hours

Specifications

| LCD | Item series | ON-TMX4 | |
|------------------|----------------------------------|--|--|
| | Display | New 4 inch IPS touch screen , 800*480 resolution | |
| Video Mode | CVBS | 1 channel BNC input & 1 channel BNC looped output, NTSC/PAL (Auto adapt) | |
| | | Analog video level meter, peak video signal level, SYNC signal level, Color bar chroma level | |
| | | measurement* | |
| | | PTZ control,RS485 control, Baud 600-115200bps,compatible with more than 30 protocols such as | |
| | | PELCO-D/P, Samsung, Panasonic etc | |
| | | CVBS loop test | the tester send and receive color bar generator signal , check BNC cable |
| | IP camera test 4K/H.265/H.264 | IP Discovery/Quick ONVIF/IPC test /RTSP play /Client APK | |
| | | Rapid Video | Auto view the video, create testing report |
| | | Hik test tool | pressing just one key to activate hikvision camera , Image test, can |
| | | | modify the user name, password and IP parameters |
| | | Dahua test tool | Dahua camera test, modify the user name, password and IP parameters |
| | IP& CVBS test | IP& CVBS test at the same time , converter test from analog to digital with dual test window | |
| | Coaxial HD test * | 8MP TVI camera test, 3840 x 2160P 15 FPS, UTC control/ call OSD menu * | |
| | | 8MP CVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control d call OSD menu * | |
| | | 5MP AHD test, 2560x1944P 12.5F/20F, UTC control d call OSD menu * | |
| | HDMI input * | 1 channel HDMI input, support 1080P * | |
| | Zoom Image | 4x zoom, to enlarge image, Screen snapshot, record, save, view and record and play back | |
| Analog Video out | color bar generator | Output one channel PAL/NTSC color bar video signal for testing monitor or video cable | |
| | 12V/2A power | Output DC12V/2A power out, supply temporarily power for the camera | |
| | PoE power output | 48V PoE power output, max power 24W | |

| Power output | | | |
|-----------------------|---|---|--|
| Cable test | TDR cable test * | BNC cable, network cable, telephone cable, RVV cable and elevator cable, cat 5/6 cable's | |
| | | length and short circuit. measurement range 1.2KM * | |
| | Cable tracer * | search BNC cable, network cable and telephone cable from the mess cables * | |
| | UTP cable test | Test UTP cable connection status and display on the screen. Read the number on the screen | |
| | RJ45 cable TDR test | test cable pair status, length, attenuation, reflectivity, impedance, skew etc. measurement range | |
| | | 180M. | |
| Tester Play | screen projection: tester, mobile phone and PC display at the same time (For android version mobile phone) | | |
| Network test | Trace route, Link monitor, DHCP server, port flashing, Ping test | | |
| Wi-Fi | Built in WIFI, speeds150M, display wireless camera image | | |
| Audio test | 1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone | | |
| Data monitor | Captures and analyzes the command data from controlling device, also can send hexadecimal | | |
| PoE test | Measurement POE switch or PSE power supply voltage and cable connection status | | |
| Drop-down menu | You can select PoE power switch, IP setting, CVBS, LAN info, HDMI IN functions etc in any interface | | |
| External power supply | DC 12V 2A | | |
| Battery | Built-in 7.4V Lithium polymer battery , 4000mAh | | |
| Rechargeable | After charging 3~4 hours, normal working time 9 hours | | |
| Operation setting | OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc | | |
| Auto off | 1-30 (mins) | | |
| Working Temperature | -10℃+50℃ | | |
| Working Humidity | 30%-90% | | |
| Dimension/Weight | 204mm x 123mm x 38mm / 0.6kg | | |
| Α | 5MP AHD test: 2560x1944P 12.5F/20F, UTC control/ call OSD menu | | |
| Н | 8MP TVI camera test: 3840 x 2160P 15 FPS, UTC control/ call OSD menu | | |
| D | 8MP CVI camera test: 3840 x 2160P 12.5/15 FPS,UTC control d call OSD menu | | |
| S | HD SDI/EX-SDI camera test: support 1080P 50/60 FPS | | |
| ٦ | Video level meter: PEAK ,SYNC signal level, color burst chroma level measurement | | |
| С | Cable tracer: Search BNC cable, network cable and telephone cable from the mess cable | | |

Note: The above data is for reference only, subject to change without prior notice.