

All in one Multi-functions CCTV tester

Model : ON-TMX7 (no SDI)

4k+h.265+8MP TVI+8MP CVI+8MP AHD+IP +CVBS + cable tracer + Analog +Video level meter

- ◆ 7 inch retina touch screen, 1920*1200 resolution
- ◆ H.265/H.264, 4K video display via mainstream
- ◆ Built in WIFI, create WIFI hotspot
- ◆ IP discovery , shortcut button, drop-down menu
- ◆ Rapid ONVIF, auto view video, and create testing report
- ◆ RJ45 TDR cable test, cable quality test
- ◆ TesterPlay, tester, android version mobile phone and PC display at the same time
- ◆ 8MP TVI, 8MP CVI, 8MP AHD test*
- ◆ Dual window test, IP & Analog camera test
- ◆ HDMI input & output, 1080p
- ◆ DC12V 2A, DC48V PoE power output
- ◆ Quick office(excel ,word ,PPT format) doc.
- ◆ Backlit buttons

The 7 inch touch screen IP camera tester is designed for maintenance and installation of IP analog, HD coaxial cameras as well as other security equipment. The 1920x1200 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. Additional, it with other functions RJ45 TDR cable test, UTP cable test and cable scan etc. CCTV installers often need to carry a variety of testing tools to complete their work. If take the all in one camera tester, making working conditions safer and increasing productivity.



Application

- CCTV system installation and maintenance
- Network cabling project installation and maintenance
- Dome camera, IPTVI CVI AHD 4K H.265 camera testing
- Video transmission channel testing
- PTZ controller

Features

1. New -7 inch retina touch screen ,1920*1200 resolution
2. New- H.264 & H.265 ,4K video display via mainstream
3. New-8MP TVI test,3840 x 2160P 15 fps,4xzoom ,video record & playback ,coaxial PTZ control & call OSD menu
4. New- 8MP AHD test, 3840x2160P 15 FPS, 4xzoom, video record & playback, coaxial PTZ & call OSD menu
5. New- 8MP CVI test, 3840 x 2160P 12.5/15fps, 4xzoom, video record & playback, coaxial PTZ & call OSD menu
6. IP & CVBS camera test ,PTZ controller
7. New- Rapid video, just by one key to detect all network cameras and auto display
8. Tester Play (screen projection): tester, mobile phone and PC display at the same time (For android version mobile phone)
9. Rapid ONVIF, auto log in and display image from the camera, activate Hikvision camera, and also can create testing report

10. New- IP and analog testing at the same time ,converter test from analog to digital with dual test window IP & CVBS
11. New- In HDMI in mode, It can converter test from analog to digital with dual test window IP & HDMI in or Analog & HDMI in
12. New- RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc
13. Cable tracer, search BNC cable, network cable and telephone cable from the mess cables
14. Improvement cable tester, UTP cable, telephone cable etc order and connectivity test, can save testing report, if special number, need to customize
15. New- Shortcut button, drop-down menu, can select PoE power ,IP setting, WLAN switch, HDMI IN functions etc in any interface
16. New- Screen lock, password lock and pattern lock are optional
17. New- HDMI signal input and output , support 1080P
18. NEW- Backlit buttons.
19. New- HDMI signal input,720×480p /720×576p /1280×720p /1920×1080p /1024×768p/1280×1024p /1280×900p /1440×900p display image ,record and snapshot
20. New- CVBS loop test, the tester send and receive color bar generator signal ,to check BNC cable
21. New- Traffic monitoring of the tester "LAN port", display network port or WIFI connection real-time upload and download speeds and other network parameters
22. New- Customers self update software ,you can install apps with android version ,such as Skype, wechat etc
23. ONVIF camera test, support 2592*1520, Network PTZ controller (ONVIF)
24. Built in Wi-Fi ,display image from the wireless camera , create WIFI hotspot
25. New- 4K video files and MKV/MP4 media files play
26. PoE DC48V power output, Max power 24W,12V /2A power output/5V 2A power output, as a power bank
27. New- Quick office, quick office app (support excel ,word ,ppt format) doc. editable
28. 8GB SD card including
29. IP discovery, it can auto-scan the whole network segment IP, and auto-modify tester's IP address
30. PTZ control supports more than 30 protocols such as PELCO-P, PELCO-D, and SAMSUNG
31. Video level meter, Video PEAK lever, SYNC level, COLOR BURST measurement
32. Enhanced Color bar generator, PAL/NTSC multi-system color bar video generator
33. POE voltage measurement, PING test ,IP address scan, port flashing etc
34. Audio in /out , support record and save the audio/LED lamp, calculators, music players and other application tools
35. 7.4 V /5000mAh Lithium Ion Polymer Battery, after 6-7 hours charging , working time lasts 10 hours

Specifications

LCD	Item series	ON-TMX7		
	Size & Display resolution	New 7 inch touch screen with retina display ,1920*1200 resolution		
Video Mode	CVBS	1 channel BNC input & 1 channel BNC looped output, NTSC/PAL (Auto adapt)		
		Analog video level meter, peak video signal level, SYNC signal level, Color bar chroma level measurement		
		PTZ control,RS485 control, Baud 600-115200bps, Compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, etc		
		CVBS loop test	Tester send and receive color bar generator signal, check BNC cable	
		Rapid Video	can create testing report	
		Hik test tool	pressing just one key to activate hikvision camera ,Image test, can modify the user name, password and IP parameters	
		Dahua test tool	Dahua camera test, modify the user name, password and IP	

		parameters
	IP& CVBS test	IP& CVBS test at the same time ,converter test from analog to digital with dual test window
	Coaxial HD test	8MP TVI camera test,3840 x 2160P 15 FPS, UTC control & call OSD menu
		8MP CVI camera test,3840 x 2160P 12.5/15 FPS,UTC control & call OSD menu
		8MP AHD camera test,3840 x 2160P 15 FPS, UTC control & call OSD menu
	HDMI input	1 channel HDMI input,support720×480p /720×576p /1280×720p /1920×1080p /1024×768p/1280×1024p /1280×900p /1440×900p/
	Zoom Image	4x zoom, to enlarge image, Screen snapshot, record ,save ,view and record and play back
Analog Video out	color bar generator	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable
HDMI output	1 channel HDMI output, support 1920*1080P	
Power output	12V/2A power output	Output DC12V/2A power out ,supply temporarily power for the camera
	PoE power output	48V PoE power output, max power 24W
	5V/2A power output	USB 5V 2A power output, as a power bank
Cable test	Cable tracer	search BNC cable, network cable and telephone cable from the mess cables
	UTP cable test	Test UTP cable connection status and display on the screen. Read the number on the screen
	RJ45 cable TDR test	Test cable pair status, length, attenuation, reflectivity, impedance, skew etc. measurement range 180M
Tester Play	screen projection: tester, android version mobile phone and PC display at the same time	
Network test	Trace route, Link monitor ,DHCP server, port flashing , Ping test	
Wi-Fi	Built in WIFI,speeds150M,display wireless camera image	
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone	
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal	
PoE test	Measurement POE switch or PSE power supply voltage and cable connection status	
Drop-down menu	You can select PoE power switch ,IP setting, WLAN switch , HDMI IN functions etc in any interface	
External power supply	DC 12V 2A	
Battery	Built-in 7.4V Lithium polymer battery ,5000mAh	
Rechargeable	After charging 5-6 hours, normal working time 10 hours	
Operation setting	OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish,Spanish etc	
Auto off	1-30 (mins)	
Working Temperature	-10℃---+50℃	
Working Humidity	30%-90%	
Dimension/Weight	255mm x 160mm x 46mm / 0.95Kg	
L	Video level meter :PEAK ,SYNC signal level, color burst chroma level measurement (free)	
C	Cable tracer:search BNC cable, network cable and telephone cable from the mess cable(free)	

The data above is only for reference and any change of them will not be informed in advance. For more detailed technical inquiries, please feel free to contact us.