



## Model : ON-A5204-5 4CH 5 in 1 DVR (AHD/TVI 5MP, CVI 4MP)



### 5 in 1 DVR Specification

Model		ON-A5204-5
Channel Mode	DVR Mode	Support, Max 4ch <b>AHD@5MP/4MP/3MP/1080P/720P</b> ; <b>TVI@5MP/4MP/3MP/1080P/720P</b> ; <b>CVI@4MP/3MP/1080P/720P</b> ;analog video real time input
	4MP/5MP	<b>AHD/TVI 5MP input, CVI 4MP input</b>
	Mixed Mode	Support, Max 4ch, Arbitrary proportion analog channels and IPCAM channel
	NVR Mode	Support, Max 4ch IPCAM video real time input
Digital Channel (IPC)	IP video input	<b>Max 4ch 3MP</b> , RJ45 interface
	built-in switch	NO
	Protocol	ONVIF,N1
	IPC Remote Setting	Time synchronization setting/ encoding setting color adjust/ Motion detection
Analog Channel	video input format	TVI 2.0(720P@25/30/50/60fps, 1080P@25/30fps, 3MP@18fps, <b>4MP@12fps/25fps/30fps, 5MP@12fps</b> ), AHD(720P@25/30fps, 1080P@25/30fps, 3MP@18fps, <b>4MP@12fps/25fps/30fps, 5MP@12fps</b> ), CVI(720P@25/30fps, 1080P@25/30fps, 3MP@18fps, <b>4MP@12fps/25fps/30fps</b> ), CVBS(960H@PAL/NTSC)
	video encoding resolution	5MP-H@12fps 4MP-H(1280*1440)@15fps 3MP(1920*1536)@12fps 1080P@15fps 1080P-H(960x1080)/720P/960H/D1@25fps;
	video encoding rate	512 Kbps -- 4Mbps
	UTC	support 4ch
	Audio input	support 4ch
	Audio encoding	G.711
	Video output	HDMI output
CVBS output		Can support custom
VGA output		1 CH , VGA Interface; Max Resolution: 1440x900
Audio output	Audio output	RCA Audio output *1, HDMI Audio output
	Stream type	AV stream/video stream
	Video Compression	H.264
	audio Compression	G.711

<b>Playback</b>	Recording	DVR mode : 4 CH 5MP-H/4MP-H/4ch3MP/4ch1080P/4ch720P Recording Mixed mode or NVR mode : 4 CH 720P/Half-1080P/1080P/3.0MP Recording
	Playback	4ch 5MP-H/4MP-H/4ch3MP/4ch1080P/4ch720P playback
<b>Double stream</b>		Support
<b>Web access</b>		Support
<b>PC</b>		Support
<b>Mobile phone</b>		Support
<b>HDD</b>	Storage Type	1 * SATA Interface
	Storage Capacity	6TB In Max
	Backup	USB Backup & Internet Backup
<b>External interface</b>	Network Interface	RJ45 10M / 100M Internet Interface
	USB Interface	2 * USB2.0 Interface(Support Upgrade,Backup,Mouse)
	Alarm interface	Optional: 4 in 1 out
	Serial Interface	1 * RS485 Interface
	APP	IPPro
<b>Other</b>	Temperature	—10°C---- 55°C
	Size	258*220*45mm
	Operation System	Embedded Linux
	Soft Power-Off	Support
	Device Control	Remote Control & Mouse
	Power Input	DC 12 V / 2A