



Model No. : **ON-AP3226-H**

Chipset	Atheros AR9341 600MHz			
Memory	DDR 64MB			
Storage	8MB Flash			
IC	SiGe2576L			
Port	10/100Mbps LAN*2			
Speed	11b: 11M , 5.5M , 2M , 1Mbps			
	11g: 54M , 48M , 36M , 24M , 18M , 12M , 9M , 6Mbps			
	11N:6.5M , 13M , 13.5M , 19.5M , 26M , 27M , 39M , 40.5M , 52M , 54M , 58.5M , 65M , 81M , 108M , 121.5M , 135M , 150M , 270M , 300Mbps			
Transmission	DSSS			
Modulation	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK			
Standard	IEEE802.11n,IEEE802.11g,IEEE802.11b,IEEE802.3u,			
Protocol	CSMA/CA,TCP/IP,IPX/SPX,NetBEUI,DHCP,NDIS3,NDIS4,NDIS5			
Channel	2312~2732MHz			
Power dissipation	≤5W			
Power	POE 24V 1A /48V 0.5A			
RF @25°C±2dB	802.11b	27±2dBm		
	802.11g	6-24Mbps	26±2dBm	
		36-48Mbps	25±2dBm	
		54Mbps	24±2dBm	
	802.11n	HT20	MCS 7	22±2dBm
		HT40	MCS 7	22±2dBm
Sensitivity	IEEE 802.11b	11Mbps ≤ -85dBm		
	IEEE 802.11g	54Mbps ≤ -70dBm		
	802.11n	HT20	MCS 7 ≤ -65dBm	
		HT40	MCS 7 ≤ -62dBm	
Antenna	Frequency	2300~2800MHz		
	Polarization	Vertical/Horizontal		
	Gain	16DBi		
Management	WEP Management	Yes		
	SNMP MIB	Yes		
	Telnet	Yes		
	Serial	Yes		
Security	MAC Address Control	No		
	Encryption	WEP 64/128bits,WPA,WPA2,802.1x		
Operating Condition	Operating Temperature	-30~65°C		
	Storage Temperature	-50~80°C		
	Humidity	≤95% (Non-condensed)		

Product Size & Weight

205*205*132.3MM

0.5kg



Package list

1 * ON-AP3226-H

1 * 24V POE power adapter 1 * Ring

1 * Bracket kit 4 * Screw

4 * Rubber stick 1 * Manual

Package size & Weight

235*225*114MM

1.0kg



Carton Size & Weight

Size : 595x470x255MM

G.W : 11.5kg

QTY : 10PCS

