





Model : ON-IPD46FTS-4X-2M 2M 4X IP outdoor mini dome PTZ Camera

Model : ON-IPD46FT-4X-5M 5M 4X IP outdoor mini dome PTZ Camera



- * 1.5 inch Vandal proof body construction,IP66.IK10
- * IR range reach up to 45 Meters
- * Pan/Tilt/Zoom ,A-B scan, tour available
- * ONVIF GB/T28181;Support P2P function
- * Support H.265/MJPEG compression,triple stream, video output
- * Compatible with HIKVISION/DAHUA/Milestone/AEVISION/UC2 and AXXON platform
- * APP : Hisee

Wall mount bracket is optional



Camera		
Model	ON-IPD46FTS-4X-2M	ON-IPD46FT-4X-5M
Video compression	H.265	H.265
Chipset+Sensor	Hi3516E+SONY307 Starlight	Hi3516E+SONY IMX335
Lens	4X f=2.8~12mm	
D/N	IR-CUT	
BLC	Auto	
WB	Auto	
S/N Ratio	>50dB	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P	
Software Control	IE, CMS, Management Platform	
audio compression	G711, PCM	
Voice intercom	optional	
Mobile View(optional)	Android iPhone	
Pan Range	0°-355°	
Tilt Range	0-70°	
Pan Speed	0-25°/s	
Tilt speed	0-20°/s	
Preset Points	220	
Guard Tours	3 groups (each group 16 preset、 dwell time and speed selectable)	
Guard Points	Max.16 points, dwell time user selectable	
AB scan range	any point in range:0°~70° and 0°-355°	
AB scan speed	1-9 grades	
Operating temperature	Outdoor: -30℃ ~ +60℃	
Operation menu	English	
Auto Control IR LED	PWM	
Support ambient light detection	4 pcs IR illumination on 1-15 grades selectable;	
IR distance	up to 45 meters	
Humidity	≤95% Non Condensing	
Consumption	≤10W	
Lightning Protection	Transient voltage 3000V	
Related validation	IP66,CE,FCC,RoHs	
Weight	NW:0.55KG GW:0.67KG	