




Model: **ON-755AHZ86A**

5MP VCA Smart AI Bullet IP camera



Features:

- 1/2.7" 5MP CMOS sensor
- 5MP HD resolution 2880*1620@25fps Smart encoding
- Ultra low illumination 0.01Lux
- 2-Exposure Line WDR upto 100dB
- Scenes switching, Day/Night (ICR), AWB, 2D/3D-DNR, Rotation 90°
- Slow Shutter, light control, White Balance, Defog
- OSD , Privacy Mask, ROI, Watermark
- Smart Intelligent Cross Line, Enter Area, Leave Area, Intrusion, People Flow Counting, Crowd Density Monitoring ,human detection, vehicle detection
- RTSP and Onvif 17.06 compatible
- Common event Motion Detection, Tampering Alarm, Audio Detection

- H.265/H.264 three-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 4 pcs Array IR Led, IR distance 70-80 meters
- HD 5-50 mm varifocal lens

Technical Specifications:

Model	ON-755AHZ86A
Camera	
Image Sensor	1/2.7" 5MP CMOS
Effective Pixels	2888H x 1628V
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	2-Exposure Line WDR upto 100dB
White Balance	Auto/Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Privacy Mask, ROI, Watermark, Low Shutter, Scenes
Encode	
Video Standard	H.264/H.265
Video Resolution	Main Stream: 25fps@5MP(2880x1620)/4MP(2560x1440), 30fps@3MP(2304x1296)/1080P Sub stream: 30fps@720P/D1/640x360/CIF Third stream: D1, 640x360,CIF
Video Bitrates	128kbps – 6144kbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
Built-in Mic	Yes
Intelligent Detection	Human Detection, Vehicle Detection Cross Line, Enter Area, Leave Area, Intrusion, People Flow Counting, Crowd Density Monitoring
IR Led	
IR Led	4 pcs Array IR Leds
IR Distance	70-80 M
Lens	
Focal length	5-50 mm varifocal Lens
Optional Function	
Built in Microphone	

Network Services	
Protocol	HTTP(s)/IPv6/TCP/UDP/RTP/RTSP/FTP/SMTP/DDNS/DHCP/PPPoE /NTP, etc.
P2P	Yes
Web	IE, Firefox, Chrome, Edge, Safari, etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	POE ,1-RJ45, 100Mbps
Power Supply	12 VDC \pm 10%
Power Consumption	< 5 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH