



APP: Superlive Plus

Hybrid 16CH H.265+ DVR

MODEL: **ON-ATR862HN**

Features :

- ▶ 8M/5M/4M/1080P/720P AHD / TVI / CVI /960H record.
- ▶ Support IP Cam record.
- ▶ H.265+ high profile compression algorithm, low bit rate, high picture quality
- ▶ Dual stream - individual network video streaming and DVR record streaming.
- ▶ Phone remote view (iPhone / iPad / Android).
- ▶ Support P2P. QR code connection.
- ▶ Device ID setup for control keyboard.
- ▶ Smart channel settings: Live / playback screen digital zoom, playback camera title and date / time position movable.
- ▶ USB or remote firmware upgrade supported.
- ▶ Convenient backup by AVI file.
- ▶ APP: Superlive Plus



Specifications :

Model	ON-ATR862HN
Sequence Display	8MP@112fps ; 5MP@320fps ; 4MP, 3MP, 1080P, 720P, WD1@480 fps
Recording Resolution	8MP @112 fps / 5MP @160 fps / 1080P(1920x1080) @480 fps / 720P/WD1(960x480)@ 480 fps IP x 8
Display Channel	1 / 4 / 6 / 8 / 9 / 16 / 25
Output	MAIN or SPOT x1 / VGA (1920x1080)x1 / HDMI(3840x2160) x1
Record Quality	Highest / Higher / Medium / Lower / Lowest
Recording Mode	Auto / manual / schedule / motion / alarm
Multi-task	Live / Record / Play / Network / Backup
Motion Detect	22 x15 grids camera for all channel
Backup	USB 3.0x1, USB 2.0x1 / Network remote backup
Storage	SATA x2 (each 10TB) / E-Sata x1
Audio / Alarm	Input : 16 ; Output : 1 / Input : 16 ; Output : 4
PTZ Control	PELCO-P, PELCO-D, CoC(UTP)
Ethernet	10/100 M Base-T
Network-Function	Support licensed CMS(100CH) / EMAP/ IE
Network Connection	TCP/IP, PPPoE, DHCP, DDNS(Auto DDNS)
Client Application	Display / Playback / Backup / DVR control / PTZ Control
Power Source	DC12V · 50Hz / 60Hz
Operating Temperature	5°C~40°C (41°F~104°F)
Dimension	380(W) x 55(H) x 270(D)mm