



Model NO.: ON-AVR8004T-NGL-V4

H.265 4CH 4K DVR with 1 SATA

APP: XMEye pro



Feature :

- Support 4ch 8M unreal-time encoding;
- Support Xvi, AHD, TVI, CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1*SATA(Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control
- Support coaxial audio
- Support human detection, face detection and other intelligence

Specification:

	Model	ON-AVR8004T-NGL-V4
System	processor	NT98331
Video	Codec	H.265+/H.265/H.264
	Preview	4ch8M@15fps(6 in 1)/4ch5M@20fps(6 in 1)/ 4ch4M(6 in 1) /4ch3M (6 in 1)/4ch1080P(6 in 1) default8M
	Encode	4ch8M@8fps(6 in 1)/4ch5M@16fps(6 in 1)/ 4ch4M@21fps(6 in 1)/4ch3M@25fps(6 in 1)/4ch1080P(6 in 1) default8M
	Decode	4ch8M@8fps(6 in 1)/4ch5M@16fps(6 in 1)/ 4ch4M@21fps(6 in 1)/4ch3M@25fps(6 in 1)/4ch1080P(6 in 1) default8M
	Multi-mode	Analog: 4ch 8M
		hybrid : 4*8M (analog) +4*8M (network)
IP:16ch 1080P/8ch 5M		
Playback	4/2/1ch	
Audio	Compression	G.711a
	coaxial audio	Support
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	4*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	1/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
General	HDD	1*SATA interface (Up to14TB)
	Temperature	0 ℃ - + 55 ℃
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W(Without HDD)
	Weight	Around1KG
Dimension	255mm(L)* 215mm(W)* 44mm(H)	