



**Model NO.: ON-AVR8004T-NMH-V4**

**H.265 4CH 5M-N DVR with 1 SATA**

**APP: XMEye pro**



### Feature :

- Support 4ch 5M-N unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 1080P output;
- Mini 1U Case, 1SATA(Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G,WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control;
- Support coaxial audio;
- Support human detection, face detection Vehicle detection and other intelligence;

## Specification:

	Model	ON-AVR8004T-NMH-V4
System	processor	NT98331
Video	Codec	H.265/H.264
	Preview	4ch5M-N@20fps ( 6 in 1 ) / 4ch4M-N@30fps ( 6 in 1 ) / 4ch1080P ( 6 in 1 ) default5M-N
	Encode	4ch5M-N@20fps ( 6 in 1 ) / 4ch4M-N@28fps ( 6 in 1 ) / 4ch1080P@25fps ( 6 in 1 ) default5M-N
	Decode	2ch5M-N@20fps ( 6 in 1 ) / 2ch4M-N@28fps ( 6 in 1 ) / 2ch1080P@25fps ( 6 in 1 ) default5M-N
	Multi-mode	Analog:4ch 5M-N
		hybrid : 4*5M-N ( analog ) +2*1080P ( network )
		IP: 16ch 1080P/8ch 5M
Playback	2ch	
Audio	Coaxial audio	support
	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	4*BNC ( Support Coaxitron )
	HDMI output	1*HDMI (MAX:1080P)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	1/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 14TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W ( Without HDD )
	Weight	Around1KG
	Dimension	255mm(L)* 215mm(W)* 44mm(H)