



Model NO.: **ON-AVR8008T-NGL**

H.265 8CH 4K DVR with 1 SATA

APP: XMEye pro



Feature :

- Support 8ch 4K unreal-time encoding;
- Support Xvi, AHD, TVI, CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1*SATA(Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control
- Support human detection, face detection and other intelligence

Specification:

	Model	ON-AVR8008T-NGL
System	processor	NT98336
Video	Codec	H.265+/H.265/H.264
	Preview	8*8M@15fps(6 in 1)/8*5M@20fps(6 in 1)/ 8*4M(6 in 1)/8*3M(6 in 1)/8*1080P(6 in 1) default :8M
	Encode	8*8M@8fps(6 in 1)/8*5M@14fps(6 in 1)/ 8*4M@18fps(6 in 1)/8*3M@21fps(6 in 1)/ 8*1080P(6 in 1) default :8M
	Decode	8*8M@8fps(6 in 1)/8*5M@14fps(6 in 1)/ 8*4M@18fps(6 in 1)/8*3M@21fps(6 in 1)/ 8*1080P(6 in 1) default :8M
	Multi-mode	Analog:8*8M
		hybrid:8*4K(analog)+8*4K(network)
		IP:16ch 16*4K/16*5M
Playback	8ch	
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	8*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX: MAX 4K)
	VGA output	1*VGA (MAX: MAX 1080P)
	Audio I/O	4/1
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to14TB)
General	Temperature	0 ℃ - + 55 ℃
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W (Without HDD)
	Weight	Around1KG
	Dimension	255mm(L)* 236mm(W)* 44mm(H)