




# Under Water 20M COLOR CAMERA

## Features:

- ⊙ 1/2.8" 2MP COMS Sensor
- ⊙ High Sensitivity ; High Performance
- ⊙ Enhanced OSD Function to adjust the image
- ⊙ Use Anode processed surface
- ⊙ **Advance design with decompression compartment**
- ⊙ Under Water down to 20 Meters
- ⊙ 14 White LEDs Illumination Range: Up to 5 Meters with color image
- ⊙ LED switched to ON/FF by Remote Controller



Decompression  
compartment



## Specification:

| Model No.              | ON-IDX333  | ON-IDX33                       |
|------------------------|--|--------------------------------|
| Effective Pixels       | 1920 * 1080 Approx. 2M Pixels                                      |                                |
| Scanning System        | Progressive  |                                |
| Sync System            | Internal Sync  |                                |
| Video Output           | 1Vpp Composite Output, 75 ohms / AHD 2.0 / CVBS                    |                                |
| Lens                   | 6mm / F1.4 Focus adjustable through UTC                            | 2.8-8mm Motorized Zoom via UTC |
| LED                    | White Light * 14   |                                |
| Resolution             | 1920 * 1080P   |                                |
| Gamma Correction       | 0.45   |                                |
| Minimum Illumination   | 0.01 Lux   |                                |
| S/N Ratio              | 65 dB (AGC Off)  |                                |
| Power Source           | DC12V  |                                |
| Power Consumption      | 12W (at LED ON)  |                                |
| Ambient                | -40 ~ 50°C / 30 ~ 90 % RH  |                                |
| Dimensions             | 104(D) x63(Φ)mm  |                                |
| Weight                 | Approx. 320g (Camera Body Only)                                    |                                |
| Backlight Compensation | Default OFF ( AREA adjustable)                                     |                                |
| White Balance          | ATW(default)/AWB /AWC->SET/Manual/Indoor/Outdoor                   |                                |
| Gain Control           | Setting through UTC / OSD menu 0~15                                |                                |
| Image Correction       | Image Reverse (Mirror) ; Sense up ; Slow Shutter                   |                                |
| Motion Detection       | 4 AREA adjustable  |                                |
| OSD Language           | English /Russia/German/Chinese/Polish/ Turkish/Portuguese/Italian. |                                |
| Picture Sharpness      | 0~10 Adj. (OSD seting)   |                                |
| Cable Length           | SR-PVC Cable 30 Meter with DC plug and Female BNC                  |                                |